

LIFE™ PLUS:
and life becomes
more beautiful
and easier!



Irritrol®

ENJOY
YOUR
LIFE™

Irritrol®

LIFE™ PLUS

The evolution of **LIFE™** is the **Plus** modular version:

up to 16 stations can be managed with the same programming module.


With **LIFE™ PLUS** it is also possible to control and program the irrigation of your garden at any time and from any place, by adding the optional **Wi-Fi** module and downloading the **Life App** on your mobile phone.



- Optimise your irrigation by connecting **LIFE™ PLUS** to the Weather broadcasting service.



- Connect your **LIFE™ PLUS** to Alexa or Google Home to manage it with simple voice commands.



- Now you can connect up to 8 **LIFE™ PLUS** with each other with a maximum limit of 48 stations!



CARATTERISTICHE PRINCIPALI

- From 4 to 16 stations
- 4 independent programs
- 6 starts per program
- Possibility of activating rain sensor via On/Off
- The sensors can be managed in 5 different modes (Off, start, stop, skip, pause)
- Water Budget from 0% to 200%
- Pulse sensor that can be activated when the valves are not working
- “Loop” program
- Possibility of working in minutes: hours or in seconds: minutes (up to 8 min)
- Rain delay option programmable for each station (from 1 sec up to 8 min)
- Multilingual display (Italian, English, French, Spanish, German)
- Optional Wi-Fi module

TECHNICAL DATA

- Flexible irrigation programming:
 - Daily
 - Weekly
 - Watering every other day
 - Irrigation at intervals of 1 to 30 days
- Rain suspension option programmable up to 31 days or “permanent”
- Overlapping programming
- Automatic, semi-automatic and manual start
- Permanent memory
- The pulse sensor is active even when the system is not in operation
- The internal “Super Cap” supplies the necessary power to keep the date and time even in the event of a power failure for over 24 hours (without the need for batteries).
- Help button to manage programming

ELECTRONICS

- Absorbed power: 220 VAC, 50 Hz;
- Power output: max. per station: 24 VAC (0.5 A); Max. Total (including MV control): 24 VAC (1.0 A)
- Operating temperature: from -10° C to 60° C

DIMENSIONS

- 186 mm x 140 mm x 67 mm (W x H x D)
- Weight: 1.5 kg

Here is our complete range: below you will find the codes which will help you for your orders... with LIFE™ PLUS success is guaranteed!

LIFE™ PLUS

PRODUCT	CODE	DESCRIPTION
	LIFE-P	Life Plus, 4-station control unit with external 220 VCA transformer
	LIFE-P-SM	4-station expansion module for Life Plus
	LIFE-P-B	4-station rear module with external 220 VAC transformer
	LIFE-MOD	Life and Life Plus programming module
	LIFE-WF	Wi-Fi module for Life and Life Plus

IT-Q/LIFE-1/22

I.S.E. Srl - Via dell'Artigianato, 1-3 - 00065 Fiano Romano (Roma) Italy
Phone (+39) 0765 40191 - Fax (+39) 0765 455386 - www.irritrol.it

Irritrol®



www.life.irritrol.it

You Tube

www.youtube.com/ISEontheweb